

# InjectPro Grout-Out

## Non-flammable, pump flush for urethane grout pumps

### CSI Div. 03

03 64 00 Injection Grouting

### Product Description:

InjectPro Grout-Out is a non-flammable, maintenance solution for urethane grout pumps, designed to clean and prime the pump and hoses before and after each use, ensuring a moisture free pumping system. InjectPro Grout-Out is solvent free, non-hazardous, non-corrosive and compatible with all Aquafin polyurethane grouts (InjectPro-CUT, InjectPro-LV and Rapidflex-213). InjectPro Grout-Out can be left in the pump and hoses during storage between use.

### Advantages:

- Zero VOC's - meets LEED criteria
- 100% solids
- Non-flammable
- Non-corrosive

Physical Properties	InjectPro Grout-Out
State	Clear liquid
Viscosity (ASTM D-1638)	100 cps
Specific Gravity (ASTM D-1475)	0.97
Flash Point (ASTM D-92)	>400°F
Boiling Point	>480°F

### Packaging:

5 gallon pails or 50 gallon drums

### Storage & Shelf Life:

Store in original sealed containers at temperature between 60°F – 90°F. Opened containers must be handled properly to prevent moisture contamination.

### Limitations:

- InjectPro Grout-Out is used to clean un-cured liquid urethane resins and has limited effect on cured polyurethane.
- Clean up spills with adequate ventilation and appropriate personal protective equipment. Cover the spill area with absorbent material such as clay or vermiculite and transfer to appropriate waste containers. Dispose of waste in accordance with federal, state and local regulations.

### Safety:

Refer to MSDS. Use rubber gloves and goggles during mixing and application. Avoid contact with eyes and skin. After contact with skin, wipe up excess liquid then wash with plenty of soap and water. In case of eye contact, rinse immediately with plenty of water and seek medical advice. Do not ingest. KEEP OUT OF REACH OF CHILDREN.

LIMITED WARRANTY: AQUAFIN, INC. warrants this product for a period of one year from the date of installation to be manufactured free of defects and to be consistent with its technical properties as stated in our current Technical Data Sheet. This product must be used as directed and within its stated shelf life. AQUAFIN INC. will replace or at our discretion refund the purchase price of any product, excluding cost of labor, which is proven to be defective. Our product recommendations are based on industry standards and testing procedures. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. We assume no warranties written, expressed or implied as to any specific methods of application or use of the product. AQUAFIN INC. MAKES NO WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED. AQUAFIN, INC. shall not be liable for damages of any sort including remote or consequential damages, down time, or delay. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

### For Professional Use Only.