

InjectPro-Oakum

Dry Oakum

CSI Div. 03

03 64 00 Injection Grouting

Product Description:

InjectPro-Oakum is a dry, twisted, jute oakum made in rope form without tar or oil. It meets Federal specifications #HHP-117-1 and NRT-0-56A, class 1. It is used in conjunction with InjectPro polyurethane grouts for many applications to stop active water leaks.

Typical Applications:

- Filling annular spaces
- Sealing joints and cracks
- Slowing water flow prior to injection

Advantages:

- Natural jute fibers with no added tar or oils
- Fast absorbency

Application:

1. Clean joint to expose clean concrete surface.
2. Cut dry InjectPro-Oakum into workable strips, typically 2-3 ft. lengths.
3. Loosen fibers with hands to enhance material absorbency.
4. Submerge dry InjectPro-Oakum into Inject-Pro polyurethane grout.
5. While removing from container, wipe excess grout material from InjectPro-Oakum.
6. Wet joint with water to prime surface before inserting saturated InjectPro-Oakum.
7. Dip saturated InjectPro-Oakum into water to start grout catalyzation.
8. Place fully saturated InjectPro-Oakum into joint.
9. Spray any visible saturated InjectPro-Oakum surface with water. If necessary, cut excess from surface of joint after cure.

Limitations:

- Wide cracks and joints sealed with urethane saturated InjectPro-Oakum may require additional injection to achieve a complete seal if excessive pressures or water flow exists.

Storage & Packaging:

Store dry. InjectPro-Oakum is available in ~50 lb rolls which consists a rope of 7-8 strands twisted together, roughly 100ft in length with ~2" diameter.

Note:

Installer is responsible for proper product application. Site visits by Aquafin personnel or representatives are solely for the purpose of making technical recommendations, not for providing supervision or quality control.

Safety:

Refer to SDS.

LIMITED WARRANTY: AQUAFIN, INC. warrants this product for a period of one year from the date of installation to be manufactured free of defects and to be consistent with its technical properties as stated in our current Technical Data Sheet. This product must be used as directed and within its stated shelf life. AQUAFIN INC. will replace or at our discretion refund the purchase price of any product, excluding cost of labor, which is proven to be defective. Our product recommendations are based on industry standards and testing procedures. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. We assume no warranties written, expressed or implied as to any specific methods of application or use of the product. AQUAFIN INC. MAKES NO WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED. AQUAFIN, INC. shall not be liable for damages of any sort including remote or consequential damages, down time, or delay. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

For Professional Use Only.



Typical application of Oakum in a leaking joint.

