

Printing date 01/31/2024

Reviewed on 01/31/2024

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**IDENTITY:** Product Name: EPOXY-GEL Fast COMPONENT A

Product Use Description: Epoxy Resin Adhesive, For Further Information, Refer to the Product Technical Data Sheet.

AQUAFIN, INC.
505 BLUE BALL RD. #160
ELKTON, MD 21921info@aquafin.net24 hr Emergency Phone: Chem-Tel (800) 255-3924
Information Phone No: (410) 392-2300
www.aquafin.net**SECTION 2: HAZARDS IDENTIFICATION**

GHS Hazard:



ROUTES OF ENTRY: EYE: YES SKIN: YES INGESTION: YES INHALATION: YES

SIGNAL WORD: WARNING!

PHYSICAL HAZARDS: Not Classified

HEALTH HAZARDS: (ACUTE AND CHRONIC)

EYES: Eye Irritant Cat. 2
SKIN: Skin Irritant Cat. 2
INGESTION: Genetic Mutagenicity Cat. 3
INHALATION: Genetic Mutagenicity Cat. 3
CARCINOGEN: IARC Cat. 2B

ENVIRONMENTAL HAZARDS:

Acute Aquatic Cat.2
Chronic Aquatic Cat.2HAZARD STATEMENTS: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H411 - Toxic to aquatic life with long lasting effects
H341 - Suspected of causing genetic defects

PRECAUTIONARY STATEMENTS:

P261 – Avoid breathing mist/vapors/spray.
P262 - Do not get in eyes, on skin, or on clothing
P264 - Wash...thoroughly after handling with soap and water.
P272 – Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment
P280 - Wear Protective gloves/protective clothing/eye protection/face protection.
P302+P352 – IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER and DOCTOR.
P333+P313 – If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 – Take off contaminated clothing and wash before reuse.
P391 – Collect spillage.
P402 – Store locked up.
P501 – Dispose of contents/container through a waste management company authorized by the local government.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Persons with preexisting skin or respiratory disorders may have their conditions aggravated by over exposure to this material.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS #:	CAL-OSHA PEL TWA (8hours)	ACGIH TLV TWA (8 hours)	Other Limits RECOMMENDED	% BY WEIGHT
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	No Data Available	No Data Available		50-70
1,3-Bis(2,3-epoxypropoxy)-2,2-dimethylpropane	17557-23-2	No Data Available	No Data Available		10-20
2,3-epoxypropyl o-tolyl ether	2210-79-9	No Data Available	No Data Available		20-30
Bisphenol-F Epoxy Resin	28064-14-4	No Data Available	No Data Available		<15
Titanium Dioxide	13463-67-7	15mg/m3	10 mg/m3		<10
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	No Data	No Data		<10

*Actual concentrations may vary due to batch to batch variation and trade secrets

SECTION 4: FIRST AID MEASURES

- EYES:** Immediately flush eyes with water for a minimum of 15 minutes while holding eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision or swelling persists, consult a physician.
- SKIN:** Remove contaminated clothing and product. Immediately wash affected area with soap and water. Do not apply greases or ointments. If skin irritation persists, consult a physician.
- INGESTION:** Rinse mouth immediately. Give small amounts of water, only if person is conscious. Only induce vomiting at the instruction of medical personnel. consult a physician
- INHALATION:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, consult a physician.

SECTION 5: FIRE-FIGHTING MEASURES

- SUITABLE EXTINGUISHING MEDIA:** Extinguish with foam, carbon dioxide, dry powder, or water fog.
- SPECIAL FIRE FIGHTING PROCEDURES:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of a fire and / or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.
- HAZARDOUS DECOMPOSITION PRODUCTS:** Hazardous decomposition products may occur when material polymerizes at temperatures above 500 °F (260 °C). Irritating and toxic gases/fumes may be released during a fire. Do not allow run-off from fire-fighting to enter drains or water courses.
- FLASH POINT:** >250 °F / 121 °C
- METHOD USED:** PMCC

SECTION 6: ACCIDENTAL RELEASE MEASURES

- PERSONAL PROTECTION:** Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillage cannot be contained.
- ACCIDENTAL RELEASE MEASURES:** In case of spill, clean up using absorbent material such as earth or sand. Small quantities can be wiped up with cloth, place cloth in leak proof container and dispose of properly.
- WASTE DISPOSAL:** Observe Federal, State and local regulations covering chemical waste spills.

SECTION 7: HANDLING AND STORAGE

- PERSONAL PROTECTION:** Use personal protective equipment to ensure product does not contact eyes or skin when handling materials.
- HANDLING AND STORAGE:** Store in cool dry place out of direct sun rays. Keep from freezing. Recommend storage temperatures range: between 40° and 95 °F (4° - 35 °C)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- PROTECTIVE MEASURE:** Wear appropriate personal protective equipment.

EYE PROTECTION: Wear appropriate safety glasses with side shields, goggles or full face shield. When working on a overhead application a full face shield is recommended.

HAND PROTECTION: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.

SKIN AND BODY PROTECTION: Wear long sleeve shirts/long pants and other clothing as required to minimize contact.

RESPIRATORY PROTECTION: Do not breathe gas/fumes/vapour/ or spray. The use of a respirator is not required during general use of this product provided adequate ventilation. If grinding or cutting cured product the use of an approved respirator is recommended.

WORK HYGIENIC PRACTICES: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

ENGINEERING CONTROLS: When using indoors, good ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

EXPOSURE LIMITS

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH (Pocket Guide)
4,4'Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane 25068-38-6	No Data Available	No Data Available	No Data Available
1,3-Bis(2,3-epoxypropoxy)-2,2-dimethylpropane 17557-23-2	No Data Available	No Data Available	No Data Available
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	No Data Available	No Data Available	No Data Available
2,3-epoxypropyl o-tolyl ether 2210-79-9	No Data Available	No Data Available	No Data Available
Trimethylolpropane triacrylate 15625-89-5	No data available	No data available	No data available
Titanium Dioxide 13463-67-7	TWA 15 mg/m3	No Data	No Data
Silicones and siloxanes, dimethyl-, reaction products with silica 67762-90-7	TWA 80 mg/m3	No Data	6 mg/m3

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White

ODOR: Mild

PHYSICAL STATE: Paste

pH AS SUPPLIED: N/D

BOILING POINT: >100 C

MELTING POINT: N/D

FREEZING POINT: N/D

VAPOR PRESSURE (mmHg): N/D

VAPOR DENSITY (AIR = 1): N/D

SPECIFIC GRAVITY (H₂O = 1): 1.3 @ 22°C

EVAPORATION RATE: Negligible

SOLUBILITY IN WATER: Negligible

PERCENT SOLIDS BY WEIGHT: 0%

PERCENT VOLATILE: Negligible

VOLATILE ORGANIC COMPOUNDS (VOC): N/D

MOLECULAR WEIGHT: N/D

VISCOSITY: 2100 Poise

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable
CONDITIONS TO AVOID (STABILITY):	Exposure to excessive heat and open flame
INCOMPATIBILITY (MATERIAL TO AVOID):	Strong acids, peroxides and other oxidizing agents.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	Normal combustion forms carbon dioxide, carbon monoxide, oxides of carbon and other organic compounds,
HAZARDOUS POLYMERIZATION:	Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

	CAS#	No data available on the product itself
Acute Oral Toxicity:		
Oral-Components		
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	LD50 >5,000 mg/kg Species: Rat
2,3-epoxypropyl o-tolyl ether	2210-79-9	LD50 5,800 mg/kg Species: Rat
1,3-Bis(2,3-epoxypropoxy)-2,2-dimethylpropane	17557-23-2	LD50 4,500 mg/kg Species: Rat
Trimethylolpropane triacrylate	15625-89-5	LC50(6hr) >0.55mg/l Rat – M/F
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	LD50 >5,000 mg/kg Species: Rat
Acute Dermal Toxicity:		
Dermal-Components		
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	LD50 20,000 mg/kg Species: Rabbit
2,3-epoxypropyl o-tolyl ether	2210-79-9	LD50 >2,000 mg/kg Species: Rabbit
Trimethylolpropane triacrylate	15625-89-5	LD50 5170mg/l Rabbit
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	LD50 >2,000 mg/kg Species: Rat
Acute Inhalation Toxicity:		
Inhalation-Components		
2,3-epoxypropyl o-tolyl ether	2210-79-9	No data available on the product itself
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	LC50(4hr): 1220 ppm Species: Rat
Skin Corrosion/ Irritation:		LC50 3.97 ml/kg Species: Rabbit
Corrosion/Irritation Components		
2,3-epoxypropyl o-tolyl ether		
Bisphenol-A - epichlorohydrin epoxy resin	2210-79-9	No data available on the product itself
Trimethylolpropane triacrylate	25068-38-6	Severe skin irritation.
	15625-89-5	Causes slight irritation.
		Rabbit – Irritating to skin 24hr
Eye Damage/Irritation:		
Damage/Irritation Components		
Bisphenol-A - epichlorohydrin epoxy resin		No data available on the product itself
2,3-epoxypropyl o-tolyl ether	25068-38-6	Causes serious eye damage.
Respiratory Damage/Irritation:	2210-79-9	Mild eye irritation.
Damage/irritation Components		No data available on the product itself
Sensitization:		
Sensitization-Components		
Trimethylolpropane triacrylate	15625-89-5	May cause sensitization by inhalation and skin contact.
2,3-epoxypropyl o-tolyl ether	2210-79-9	May cause sensitization by skin contact.
Germ Cell Mutagenicity		The product or a component may be mutagenic, the data is inconclusive.
Maternal Toxicity:		No data available on the product itself

Carcinogenicity:**ACGIH:** No data**IARC:** TiO2: IARC Group 2B carcinogen "possibly carcinogen to humans".

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possible carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form. It does not pose a dust hazard; therefore, **this classification is not relevant**. Note: sanding of this product will create a possible dust hazard.

NTP No data**OSHA** No data**SECTION 12: ECOLOGICAL INFORMATION****ECOTOXICITY:****CAS#**

Aquatic toxicity:		No data on product itself
Toxicity to Fish-Components		
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	LC50(96hr) 1.5mg/l Species: Salo Gairdneri
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	LC50(96hr) 0.5mg/l Species: Oncorhynchus mykiss
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	LC50(96hr) 10,000 mg/l Species: Brachydanio rerio
Toxicity to Algae-Components		
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	EC50(72hr) 1.8mg/l Species: elenastrum capricornutum
Toxicity-Aquatic Invertebrates		
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	EC50(48hr) 2.7mg/l Species: Daphnia Magna
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	EC50(24hr) >1,000 mg/l Species: Daphnia magna
Toxicity to other organisms:		

PERSISTENCE & DEGRADABILITY:**BIODEGRADABILITY:**

Biodegradability-Components		No data available on product itself
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	Not readily biodegradable 5% 28 days
1,3-Bis(2,3-epoxypropoxy)-2,2-dimethylpropane	17557-23-2	Not easily biodegradable

BIOACCUMULATIVE POTENTIAL:

BioAccumulative-Components:		No data available on product itself
Bisphenol-A - epichlorohydrin epoxy resin	25068-38-6	Low potential to bioaccumulate BCF = 31
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	LogP _{ow} : 3.

MOBILITY IN SOIL:

NDA

OTHER ADVERSE EFFECTS:

NDA

AQUATIC RELEASE:

Advise authorities if product has entered or may enter watercourses or sewer drains.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Do not allow this material to drain into sewers / waterways, ditches, containment pools or water supplies. Dispose of contents / containers in accordance with local/regional/international regulations.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

PROPER SHIPPING NAME:
HAZARD CLASS:
ID NUMBER: Not Regulated for transportation
PACKING GROUP:
LABEL STATEMENT:

WATER TRANSPORTATION (IMDG)

PROPER SHIPPING NAME: Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin Mixture), Marine Pollutant
HAZARD CLASS: 9
ID NUMBER: UN3082
PACKING GROUP: III
LABEL STATEMENT: Marine Pollutant

AIR TRANSPORTATION (IATA / ICAO)

PROPER SHIPPING NAME: Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin Mixture) , Marine Pullutant
HAZARD CLASS: 9
ID NUMBER: UN3082
PACKING GROUP: III
LABEL STATEMENT: Marine Pollutant

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT):
**CERCLA (COMPREHENSIVE RESPONSE
COMPENSATION, AND LIABILITY ACT):**

OSHA: 29 CFR 1910.1200 (Hazard Communication required)
WHMIS Class D-2B

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

302/304	N/A	
311/312 HAZARD CATEGORIES:	Acute Health Hazard:	Yes
	Chronic Health Hazard:	Yes
	Fire Hazard:	No
	Pressure Release Hazard:	No
	Reactivity Hazard:	No
313 REPORTABLE INGREDIENTS:	N/A	

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65 (THE SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT of 1986)

This product does not contain known levels of any chemicals known to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	
HMIS HAZARD RATING	
HEALTH	2
FLAMMABILITY	1
REACTIVITY	1
PERSONAL PROTECTION	C
4 – Severe, 3 – Serious, 2 – Moderate, 1 – Slight	
C – (Safety glasses, gloves, apron)	

The information provided herein was believed to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use.