

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

### \* 1 Identification

- **Product Identifier**
- **Trade name: EPOXY-SLV Component B**
- **Relevant identified uses of the substance or mixture and uses advised against:**  
No further relevant information available.
- **Product Description** Low viscosity epoxy resin
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
Aquafin Inc.  
505 Blue Ball Road #160  
Elkton, MD 21921  
Phone: 410-392-2300  
Fax: 410-392-2324  
Email: info@aquafin.net  
Web: www.aquafin.net
- **Emergency telephone number:**  
Chemtrec at 1-800-424-9300 24 Hours  
Outside the U.S., call Chemtrec collect at 703-527-3887

### 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



GHS08 Health hazard

Repr. 2                      H361 Suspected of damaging fertility or the unborn child.

---



GHS05 Corrosion

Skin Corr. 1B              H314 Causes severe skin burns and eye damage.  
Eye Dam. 1                H318 Causes serious eye damage.

---



GHS09 Environment

Aquatic Acute 1            H400 Very toxic to aquatic life.  
Aquatic Chronic 1        H410 Very toxic to aquatic life with long lasting effects.

---



GHS07

Acute Tox. 4                H302 Harmful if swallowed.  
Skin Sens. 1                H317 May cause an allergic skin reaction.

---

- **Label elements:**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**
**Hazard pictograms:**


GHS05 GHS07 GHS08 GHS09

**Signal word:** Danger

**Hazard-determining components of labeling:**

4-nonylphenol, branched  
 2-piperazin-1-ylethylamine  
 2,4,6-tris(dimethylaminomethyl)phenol  
 4,4'-methylenebis(cyclohexylamine)

**Hazard statements:**

H302 Harmful if swallowed.  
 H314 Causes severe skin burns and eye damage.  
 H317 May cause an allergic skin reaction.  
 H361 Suspected of damaging fertility or the unborn child.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statements:**

P260 Do not breathe dusts or mists.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P280 Wear protective gloves.  
 P280 Wear eye protection / face protection.  
 P273 Avoid release to the environment.  
 P264 Wash thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
 P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P363 Wash contaminated clothing before reuse.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P391 Collect spillage.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Unknown acute toxicity:**

94 % of the mixture consists of component(s) of unknown toxicity.

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

### Trade name: EPOXY-SLV Component B

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMS-ratings (scale 0 - 4)**

HEALTH	*4	Health = *4
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Hazard(s) not otherwise classified (HNOC):** None known

### 3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous Components:**

CAS: 84852-15-3	4-nonylphenol, branched ⚠ Repr. 2, H361; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302	≥85%
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	2-12%
CAS: 140-31-8 RTECS: TK 8050000	2-piperazin-1-ylethylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Flam. Liq. 4, H227; Aquatic Chronic 3, H412	2-12%
CAS: 9046-10-0	Poly(propylene glycol) bis(2-aminopropyl ether) ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	2-12%
CAS: 1761-71-3	4,4'-methylenebis(cyclohexylamine) ⚠ Acute Tox. 3, H301; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318	2-12%

### 4 First-Aid Measures

- **Description of first aid measures:**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.
- **After inhalation:**  
In case of unconsciousness place patient stably in side position for transportation.  
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

### 5 Fire-Fighting Measures

- **Extinguishing media:**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture:** No further relevant information available.
- **Advice for firefighters:**
- **Protective equipment:**  
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Avoid contact with skin, eyes and clothing  
Avoid breathing fume/gas/mist/vapors/spray.  
Do not take internally.  
Use personal protection equipment as outlined in section 8.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep protective respiratory device available.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool, dry place.  
Store in a well ventilated place.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

### 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing and wash before reuse.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Penetration time of glove material:**  
The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.
- **Eye protection:**



Tightly sealed goggles

### 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Amber
- **Odor:** Distinctive
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

<b>Melting point/Melting range:</b>	Not determined.
<b>Boiling point/Boiling range:</b>	Not determined.
- **Flash point:** 150 °C (302 °F)

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:**
  - Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
  - Relative density:** Not determined.
  - Vapor density:** Not determined.
  - Evaporation rate:** Not determined.
- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 0.0 %
- **Other information:** No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**
  - Strong oxidizing agents.
  - Strong acids, strong bases
- **Hazardous decomposition products:** Carbon dioxide, carbon monoxide and nitrogen oxides.

### 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>9046-10-0 Poly(propylene glycol) bis(2-aminopropyl ether)</b>		
Oral	LD50	2885.3 mg/kg (rat)
Dermal	LD50	2980 mg/kg (rabbit)
Skin - rabbit - Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days. - OECD Test Guideline 404.		

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

Inhalative	LC50/4 h	>0.74 mg/l (rat) (8 hours)
<ul style="list-style-type: none"> <li>· <b>Primary irritant effect:</b></li> <li>· <b>On the skin:</b> Strong caustic effect on skin and mucous membranes. May cause an allergic skin reaction.</li> <li>· <b>On the eye:</b> Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation.</li> <li>· <b>Sensitization:</b> Sensitization possible through skin contact.</li> <li>· <b>Additional toxicological information:</b> The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Corrosive Irritant Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.</li> <li>· <b>Carcinogenic categories:</b></li> </ul>		
<ul style="list-style-type: none"> <li>· <b>IARC (International Agency for Research on Cancer):</b> None of the ingredients are listed.</li> </ul>		
<ul style="list-style-type: none"> <li>· <b>NTP (National Toxicology Program):</b> None of the ingredients are listed.</li> </ul>		
<ul style="list-style-type: none"> <li>· <b>OSHA-Ca (Occupational Safety &amp; Health Administration):</b> None of the ingredients are listed.</li> </ul>		

**12 Ecological Information**

- **Toxicity:**
- **Aquatic toxicity:**  
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Must not reach bodies of water or drainage ditch undiluted or unneutralized.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

### 13 Disposal Considerations

- **Waste treatment methods:**
- **Recommendation:**  
It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.  
Do not allow product to reach sewage system.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR, IMDG, IATA** UN1760
- **UN proper shipping name:**
- **DOT** Corrosive liquids, n.o.s. (4-nonylphenol, branched)
- **ADR** UN1760 Corrosive liquids, n.o.s. (4-nonylphenol, branched),  
ENVIRONMENTALLY HAZARDOUS
- **IMDG** CORROSIVE LIQUID, N.O.S. (4-nonylphenol, branched),  
MARINE POLLUTANT
- **IATA** CORROSIVE LIQUID, N.O.S. (4-nonylphenol, branched)
- **Transport hazard class(es):**

· **DOT**



- **Class:** 8 Corrosive substances
- **Label:** 8

· **ADR**



- **Class:** 8 (C9) Corrosive substances
- **Label:** 8

· **IMDG**



- **Class:** 8 Corrosive substances
- **Label:** 8

(Contd. on page 9)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

**· IATA**



- **Class:** 8 Corrosive substances
- **Label:** 8
- **Packing group:** II
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:** Product contains environmentally hazardous substances: 4-nonylphenol, branched
- **Special marking (ADR):** Symbol (fish and tree)
- **Special precautions for user:** Warning: Corrosive substances
- **Danger code (Kemler):** 80
- **EMS Number:** F-A,S-B
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: 1 L  
On cargo aircraft only: 30 L
- **Remarks:** Special marking with the symbol (fish and tree).

---

- **ADR**
- **Excepted quantities (EQ):** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

---

- **IMDG**
- **Limited quantities (LQ):** 1L
- **Excepted quantities (EQ):** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN1760, Corrosive liquids, n.o.s. (4-nonylphenol, branched), ENVIRONMENTALLY HAZARDOUS, 8, II

**15 Regulatory Information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

<ul style="list-style-type: none"> <li>· <b>Section 355 (extremely hazardous substances):</b></li> </ul>	None of the ingredients are listed.
----------------------------------------------------------------------------------------------------------	-------------------------------------

<ul style="list-style-type: none"> <li>· <b>Section 313 (Specific toxic chemical listings):</b></li> </ul>	None of the ingredients are listed.
------------------------------------------------------------------------------------------------------------	-------------------------------------

<ul style="list-style-type: none"> <li>· <b>TSCA (Toxic Substances Control Act):</b></li> </ul>	All ingredients are listed or exempt from listing.
-------------------------------------------------------------------------------------------------	----------------------------------------------------

<ul style="list-style-type: none"> <li>· <b>California Proposition 65:</b></li> </ul>	
---------------------------------------------------------------------------------------	--

<ul style="list-style-type: none"> <li>· <b>Chemicals known to cause cancer:</b></li> </ul>	None of the ingredients are listed.
---------------------------------------------------------------------------------------------	-------------------------------------

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

**Trade name: EPOXY-SLV Component B**

<ul style="list-style-type: none"> <li>· <b>Chemicals known to cause reproductive toxicity for females:</b></li> </ul>
<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> <li>· <b>Chemicals known to cause reproductive toxicity for males:</b></li> </ul>
<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> <li>· <b>Chemicals known to cause developmental toxicity:</b></li> </ul>
<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> <li>· <b>Carcinogenic categories:</b></li> </ul>
<ul style="list-style-type: none"> <li>· <b>EPA (Environmental Protection Agency):</b></li> </ul>
<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> <li>· <b>TLV (Threshold Limit Value established by ACGIH):</b></li> </ul>
<p>None of the ingredients are listed.</p>
<ul style="list-style-type: none"> <li>· <b>NIOSH-Ca (National Institute for Occupational Safety and Health):</b></li> </ul>
<p>None of the ingredients are listed.</p>

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS05   GHS07   GHS08   GHS09

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

- 4-nonylphenol, branched
- 2-piperazin-1-ylethylamine
- 2,4,6-tris(dimethylaminomethyl)phenol
- 4,4'-methylenebis(cyclohexylamine)

· **Hazard statements:**

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements:**

- |      |                                                                           |
|------|---------------------------------------------------------------------------|
| P260 | Do not breathe dusts or mists.                                            |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray.                          |
| P280 | Wear protective gloves.                                                   |
| P280 | Wear eye protection / face protection.                                    |
| P273 | Avoid release to the environment.                                         |
| P264 | Wash thoroughly after handling.                                           |
| P270 | Do not eat, drink or smoke when using this product.                       |
| P272 | Contaminated work clothing must not be allowed out of the workplace.      |
| P201 | Obtain special instructions before use.                                   |
| P202 | Do not handle until all safety precautions have been read and understood. |

(Contd. on page 11)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

### Trade name: EPOXY-SLV Component B

- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P363 Wash contaminated clothing before reuse.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision:** 06/01/2016 / 4

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Flam. Liq. 4: Flammable liquids – Category 4  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 12)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/01/2016

Reviewed on 06/01/2016

### Trade name: EPOXY-SLV Component B

Repr. 2: Reproductive toxicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106