

SAFETY DATA SHEET SDS No. R.B.1

Date prepared: DECEMBER 2015 Date revised: JANUARY 2019

SDS No.R.B.1

Section 1 – Product Identification

Product Name:

REBAR-PRIMER/BOND-CI

Chemical Characterization: Product Use Description:

Cement – Preparation Cement based underlayment

AQUAFIN, INC. 505 BLUE BALL RD. #160 ELKTON, MD 21921 Emergency Phone No.(800) 394-1410Information Phone No.(410) 392-2300www.aquafin.net

Section 2 – Hazards Identification

GHS Classification:

IDENTITY:

Skin irritation, Category 2H315:Causes skin irritation (alkaline when moistened)Serious eye damage, Category 1H318:Causes serious eye damageRespiratory system; Category 3H335:May cause respiratory irritationCarcinogenity, Category 1AH350:May cause cancer

info@aquafin.net

GHS Label element:

Hazard Pictograms



Signal Word:	Danger		
Hazard Statements: H315: H318: H335: H350:	Causes seriou	ritation (alkaline when moistened). s eye damage. piratory irritation. ncer.	
Precautionary Stateme	nts:		
Prevention:		and the floor to a life of	
P264:		Wash skin thoroughly after handling.	
P280: P280:	Wear eye protection/face protection. Wear protective gloves.		
P281:	Use protective equipment as required.		
	[- 1h	
Response:			
P302 + P352:	IF ON SKIN:	Wash with plenty of water.	
P304 + P340:	IF INHALED:	Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
P305 + P351 + P338:	IF IN EYES:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308 + P313	IF exposed or concerned. Get medical advice/attention.		
P332 + P313:	IF skin irritation occurs" Get medical advice/attention.		
D262.	Take off conteminated elething and weak before rouse		



Stora	ae:	
otoru		

B 4 6 6 B 6 6 6 6	
P403 + P232:	Store in a well-ventilated place. Protect from moisture.
	•

Disposal:

P501:	Dispose of contents/container to an approved waste disposal site.
P502:	Refer to manufacturer/supplier for information on recovery/recycling.

Section 3 – Composition / Information on Ingredients

Product based on cement and mineral filler.

Hazardous Components	CAS No.	TLV	PEL	Weight %
Portland Cement	65997-15-1	10 mg/m ³	5 mg/m ³	40 - 80
Crystalline Quartz Silica (SiO ₂)	14808-60-7	0.05 mg/m^{3}	0.1 mg/m^3	20 - 40
Proprietary Formula Enhancing Additives				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence not require reporting in this section.

Section 4 – First Aid Measures

After Inhalation:	Remove subject to fresh air. Administer oxygen if difficulty with breathing. Consult a physician.
After Ingestion:	Immediately seek medical attention. Do not induce vomiting without medical advice. If conscious, drink plenty of water.
After Skin Contact:	Instantly wash skin with plenty of soap and water for at least 15 minutes. Wash clothing before reuse. Seek medical attention if symptoms persist.
After Eye Contact:	Rinse opened eye with plenty of running water for at least 15 minutes, lifting upper and lower eyelids occasionally. Consult physician.

Section 5 – Fire Fighting Measures

Extinguishing Media:	Carbon dioxide (CO ₂), extinguishing powder, water fog, alcohol- resistant foam.
Special Fire Fighting Procedures:	As in any fire, wear full protective gear and NIOSH-approved self- contained breathing apparatus with full face-piece operated in the pressure demand or other positive pressure mode.
Unusual Fire and Explosion Hazards	No unusual fire or explosion hazards. Material can splatter above 212°F (100°C).

Person-related Safety Precautions:	Avoid causing dust. Avoid eye and skin contact.
Environmental precautions:	Prevent material from reaching sewage and drainage systems or bodies of water.
Methods for Cleaning up:	Use dry cleanup methods that do not disperse dust into the air. With water, material hydrates to a solid harmless waste. Wear personal



protective equipment. Emergency procedures are not required.

Section 7 – Handling and Storage

- Handling: Avoid causing dust. Avoid eye and skin contact. Keep out of reach of children.
- **Storage:** Store in a cool, dry enclosed area off the ground in tightly closed containers. Protect against wetness and water. No special measures required against explosion and fires. Store away from foodstuffs.

Section 8 – Exposure Controls / Personal Protection

Engineering Controls:	Use with adequate general and local exhaust ventilation. Washing of the skin in the working area must be possible. Eye-wash bottle must be available.
Respiratory Protection:	Wear a properly fitted NIOSH approved respirator in poorly ventilated areas and/or if high dust concentrations are encountered.
Skin Protection:	When installing, wear appropriate protective rubber or plastic gloves to prevent hand-skin exposure. Wear appropriate impervious clothing to prevent skin exposure (long sleeve shirt and long pants).
Eye Protection:	Wear tightly sealed safety glasses with side shields or goggles. Face shield as necessary.
Work/Hygienic Practices:	Wash hands before breaks and after work, and before eating, drinking or smoking.

Section 9 – Physical and Chemical Properties

Physical State:	Powder
Appearance/Color:	Cement / gray
Odor:	Weak, characteristic
Solubility in water:	Fully miscible
Boiling Point:	N/A
Melting Point:	N/A
Flash Point:	Not combustible
Auto ignition:	N/A
Bulk Density:	approx. 1.4 kg/dm ³ @ 68°F (20°C)
pH (in water):	11 – 13.5 (Alkaline)
VOC Concentration:	0 g/l

Section 10 – Stability and Reactivity

Chemical Stability:	Stable under normal temperatures and pressures.
Conditions to Avoid:	Avoid contact with humidity. Product hydrates (hardens) and becomes unusable.
Hazardous Decomposition Products: No decomposition if used according to specifications.	
Hazardous Polymerization:	Will not occur.
Incompatibilities:	None known.



Section 11 – Toxicological Information

Acute Inhalation Toxicity: <u>Product</u> Silica, crystalline quartz Portland cement	<u>Type</u> LC50 LC50	<u>Value</u> no data available no data available	
Acute Oral Toxicity: Silica, crystalline quartz Portland cement	LC50 (Oral) LC50 (Oral)	1,300 mg/kg 2,000 mg/kg	
Acute Dermal Toxicity Silica, crystalline quartz Portland cement	LC50 (Dermal) LC50 (Dermal)	no data available no data available	
Primary Irritant Effect:On the skin:On the eye:	On the skin: Irritant for skin and mucous membranes		

On the eye: Irritant effect
Sensitization: No sensitizing effect known.

Section 12 – Ecological Information

- **Ecological Information:** The unused product is slight water pollutant. Large quantities may be toxic to fish. Do
 - not allow undiluted product or large quantities to reach into waterways or drains.

Section 13 – Disposal Considerations

Waste Disposal Method:	Dispose of in a manner consistent with federal, state and local regulations. Do not dispose together with household garbage. Do not allow product to reach sewage system.	
Unused Residue or Dry Spilla	ige: Pick up dry material. Possibly reuse depending on amount of contamination. Prevent dust exposure. In case of disposal, harden with water and dispose in accordance to local regulations.	
Slurries:	Allow to harden and dispose of as described above.	
Container disposal:	Completely emptied packaging can be given for recycling.	

Section 14 – Transport Information

RCRA Hazard Class:	Non-hazardous
USDOT (Domestic Surface)	Not regulated
IMDG (Ocean) Hazard Class or Division:	Not regulated
IATA/ICAO (Air) Hazard Class or Division:	Not regulated
TDG (Canada):	Not regulated
UN Number:	Not listed

Section 15 – Regulatory Information

Acute Health: Chronic Health: YES YES

SARA Section 313 Notification:		This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 or CFR 372.				
CERCLA:	No CERCLA chemicals exist in this product above reporta concentrations.					
TSCA Section 12(b) Export Notification: There are no reportable TSCA 12(b) Chemicals in this product.						
State Regulations:	<u>State RTK</u> MA, NJ, PA MA, NJ, PA	<u>CAS Number</u> 65997-15-1 14808-60-7	<u>Chemical name</u> Cement, Portland, chemicals Silica, crystalline quartz			
California Propositior	ı 65:	Warning – This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm: CAS 14808-60-7: Silica, crystalline quartz.				
Section 16 – Other Information						

(Hazard Rating:	0 = Minimal;	1 = Slight;	2 = Moderate;	3 = Serious;	4 = Severe; * = Chronic)		
HMIS III rating Health: 2*	j: Flammability:	0 Physic	al hazard: 0				
Abbreviations and acronyms:							
USDOT:United States Department of Transportation.IMDG:International Maritime Code for Dangerous Goods.IATA:International Air Transport Association.CAS:Chemical Abstracts Service (Division of the American Chemical Society).LC50:Lethal concentration, 50 percent.LD50:Lethal dose, 50 percent.							

SDS prepared by:

Aquafin product safety department.

DISCLAIMER:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. Aquafin shall not be responsible for the use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. User is responsible for determining appropriate safety measures and for applying the legislation covering his own activities. We recommend that user makes tests to determine the suitability of a product for its particular purpose prior to use.

END OF SDS

(January 22, 2019)